

YF-8123 Payment Terminal



YF-8123 Payment Terminal

Rating: Not Rated Yet

Price

Price with discount

Salesprice with discount

Sales price

Discount

Tax amount

[Ask a question about this product](#)

Description

Based upon Android system, embedded technology and mobile Internet technology, YF-8123 completely changes traditional POS modes and provides infinite possibilities for mobile big data and third party integration.

Applications:

Financial device: store sales terminals, bank self-service terminals, and market checkout terminals.

Features:

- Provide driver program, dynamic library, API function or control in detail
- Provide test acceptance program
- Equip with YF-8123 program downloader and YF-8123 password downloader to upgrade program security and transmit password security

- Accept client's related application software or middleware's development

Item	Specificati on
Processor	ARM Cortex A7, 1.1GHz, 4 Core Processor
Memory	1GB DDR3 SDRAM, 8GB EMMC
System	Android 5.1
Magnetic card reader	Track 1/2/3, Bi- directional, ISO7810, ISO7811, ISO7813
Smart Card Reader	Support 1.8V, 3.3V, 5V card Support Memory card, CPU card EMV L1 & L2, PBOC3.0, ISO7816
Contactles s card reader	standard 13.56MHz, 14443 Type A/B
SIM card	QPBOC3.0 standard and EMV contactless standard Support

slot 1.8V and
3V

Mobile communication Support GSM, WCDMA, EVDO, TDSCDMA, TDD-LTE, FDD-LTE

WIFI Standard: 802.11b/g/n
GPS Support built-in GPS and Beidou, GLONASS, Galileo system, LBS positioning

Audio Support built-in speakers and audio play

LED 4 led meet the Union pay contactless reader standard

Display 5.5" 1280*720 pixel, LCD, backlight control, signal strength, battery status

Printer Support multipoint capacitance touch, and touch operation
High-speed thermal printer; printing speed: 16 lines/s, paper width: (57.5±0.5) mm

Physical key 1 ON/OFF key, sound control key

Camera Rear: Flash, Auto-Focus, 5million pixels

Port Front: 2 million pixels, support common one-dimensional bar code & two-dimensional bar code scanning

1 Micro USB OTG interface, USB 2.0HS standard

1 SIM card slot

2 PSAM card slot

Power	1 Micro SD card slot, Supports up to 32GB Input: 100-240VAC 50Hz; Output: 5V 2A DC; Micro-USB standard charging port
Battery	Long lasting lithium battery, 5000mAh, 3.7V
Environmental	Working temperature: -10°C~50°C Relative humidity: 10%-90% (non- condensation) Storage temperature: -20°C~80°C
Certification	PCI 4.x Contact EMV L1&L2 certification Contactless EMV L1 certification CCC certification Telecommunication equipment network access license Wireless transmitting equipment approval

Reviews

There are yet no reviews for this product.